

SOFAR 3K~6KTLM-G3

3 / 3.6 / 4 / 4.6 / 5 / 6 kW

SINGLE-PHASE DUAL MPPT



Product advantages

- Max. efficiency up to 98.4%
- Compact design, lightweight
- Two MPPTs with 150% DC overload
- Natural cooling, no fans, low noise
- Feed-in limitation function
- RS485/Bluetooth, Optional: WiFi/Ethernet



Model	SOFAR 3KTLM-G3	SOFAR 3.6KTLM-G3-J	SOFAR 4KTLM-G3	SOFAR 4.6KTLM-G3	SOFAR 5KTLM-G3	SOFAR 5KTLM-G3-A	SOFAR 6KTLM-G3
Input (DC)							
Max. input voltage	600V						
Rated input voltage	500V						
Start-up voltage	90V						
MPPT operating voltage range	80V-550V						
Number of MPPT trackers	2						
Number of DC inputs	1 for each MPPT						
Max. input MPPT current	15A/15A						
Max. input short circuit current	22.5A/22.5A						
Output (AC)							
Rated output power	3000W	3600W	4000W	4600W	5000W	5000W	6000W
Max. apparent power	3300VA	3600VA	4400VA	4600VA	5500VA	5000VA	6000VA
Max. output current	15A	16A	20A	25A	25A	21.7A	29A
Rated output voltage	UNPE 230VAC						
Output voltage range	180VAC-270VAC						
Rated output frequency	50/60Hz						
Output frequency range	45Hz-65Hz/50Hz-65Hz						
Active power adjustable range	0-100%						
THDi	<3%						
Power factor	1 (adjustable +0-8)						
Efficiency							
Max. efficiency	98.2%	98.2%	98.2%	98.4%	98.4%	98.4%	98.4%
European efficiency	97.5%	97.5%	97.5%	97.5%	97.5%	97.5%	97.5%
Protection							
DC reverse polarity protection	Yes						
Anti-islanding protection	Yes						
Leakage current protection	Yes						
Ground fault monitoring	Yes						
PIV-array string fault monitoring	Yes						
DC switch	Yes						
SPD	PVI type III AC type III						
General Data							
Ambient temperature range	-50°C-60°C						
Self-consumption at night	<1W						
Topology	Transformerless						
Degree of protection	IP65						
Allowable relative humidity range	0-100%						
Max. operating altitude	4000m						
Cooling	Natural						
Dimension (WHHD)	349-344x168mm						
Weight	9.2kg						
Display	LCD & Bluetooth APP						
Communication	RS485/WIFI						
Standard	IEC/EN 61000-6-2/3, IEC/EN 61000-3-1/17, IEC 62116, IEC 61727, IEC 61683, IEC 60068-1/2/14/20, IEC/EN 62109-1/2, VDE 0410-1, CEI 0-21, C10/11, UNE 217002, 2020, GB 6099, EN 50549-1, ANRE 208						

*SOFAR 3.6KTLM-G3-J is only for Jordan.

**All specifications are subject to change without notice.