

SOFAR 3.3K~12KTLX-G3

3.3 / 4.4 / 5.5 / 6.6 / 8.8 / 11 / 10 / 12 kW

THREE-PHASE DUAL MPPT



Product advantages

- Maximum efficiency 98.6%
- Low start-up voltage, wide MPPT voltage
- Maximum DC input voltage 1100 V
- Smart string level monitoring
- Remote firmware upgrade
- Natural cooling, no fans, low noise
- Type II SPD for both DC and AC side



Model	SOFAR 3.3KTLX-G3	SOFAR 4.4KTLX-G3	SOFAR 5.5KTLX-G3	SOFAR 6.6KTLX-G3	SOFAR 8.8KTLX-G3	SOFAR 11KTLX-G3	SOFAR 10KTLX-G3-A	SOFAR 12KTLX-G3
Input (DC)								
Max. input voltage	1100V							
Rated input voltage	650V							
Startup voltage	160V							
MPPT operating voltage range	140V~1000V							
Number of MPPT trackers	2							
Number of DC inputs	1/1							
Max. input MPPT current	15A/15A							
Max. input short circuit current	22.5A/22.5A							
Output (AC)								
Rated output power	3000W	4000W	5000W	6000W	8000W	10000W	10000W	12000W
Max. apparent power	3300VA	4400VA	5500VA	6600VA	8800VA	11000VA	10000VA	13200VA
Max. output current	5A	6.7A	8.3A	10A	13.3A	16.7A	15.2A	20A
Rated output voltage	3/N/PE, 230/400Vac							
Output voltage range	310Vac~400Vac							
Output frequency	50/60Hz							
Output frequency range	45Hz~55Hz/53Hz~65Hz							
Active power adjustable range	0~100%							
THDI	<3%							
Power factor	1 (adjustable± 0.9)							
Efficiency								
Max. efficiency	98.40%	98.40%	98.40%	98.40%	98.50%	98.50%	98.50%	98.50%
European efficiency	97.50%	97.50%	97.50%	97.50%	98.00%	98.00%	98.00%	98.00%
Protection								
DC reverse polarity protection	Yes							
Anti-islanding protection	Yes							
Leakage current protection	Yes							
Ground fault monitoring	Yes							
PIV-array string fault monitoring	Yes							
DC switch	Yes							
SPD	PIV type II AC type II							
General Data								
Ambient temperature range	-50°C~+60°C							
Self-consumption at night	<1W							
Topology	Transformerless							
Degree of protection	IP65							
Allowable relative humidity range	0~100%							
Max. operating altitude	4000m							
Cooling	Natural							
Dimension (W*H*D)	430*353*182mm							
Weight	17kg	18kg						
Display	LCD & Bluetooth APP							
Communication	RS485/WIFI							
Standard	IEC 61000-4-1/2, IEC/EN 61000-3-2/3, IEC/EN 61000-3-11/12, IEC 62116, IEC 62116, IEC 61727, IEC 61853, IEC 60068-1/2/10/30, IEC/EN 62105-1/2, GB/T 9476, GB/T 19814, VDE V0106-1, EN 50549-1, UNE 217002-2020							

*All specifications are subject to change without notice.